

Quickramps







- 12 mm - 825037.12

- 16 mm - 825037.16

- 20 mm - 825037.20

- 28 mm - 825037.28

- 4 mm - 825037.4

- 40 mm - 825037.40

- 52 mm - 825037.52

- 60 mm - 825037.60

- Quickramp x 25 (only) - 825038.25

- Quickramp x 4 (only) - 825038.4

- Quicktape x25 (only) - 825039

- 8 mm - 825037.8

Ramps for small thresholds, easy to install and clean

Quickramps are made from a single piece measuring 100 cm wide and can be easily cut to fit the width of various thresholds. Installation is very simple. Either by simply using double-sided adhesive tape (quick tape), or by first attaching quick pads (4 for a width of 100 cm) and clipping the ramp onto them. The quick pads can be glued or screwed to the floor.

It is possible to choose from a range of heights to acquire the exact the passage height required

Available models:

- Height 4 mm : Depth : 5 cm.

Weight: 0.12 kg

- Height 8 mm: Depth: 7.5 cm.

Weight: 0.27 kg

- Height 12 mm : Depth : 12.5 cm.

Weight: 0.58 kg

- Height: 16 mm. Depth: 12.5 cm.

Weight: 0.88 kg

- Height: 20 mm. Depth: 15 cm.

Weight: 1.10 kg

- Height: 28 mm. Depth: 17.5 cm. Weight: 1.80 kg

- Height: 40 mm. Depth: 25 cm.

Weight: 3.70 kg

- Height 52 mm. Depth: 30 cm.

Weight: 5.70 kg
- Height: 60 mm. Depth 32.5 cm.

Weight: 7.15 kg

Maximum user weight: 2000 kg

Installation system:

- Quickpads : Set of 4. Per fastener.

- Quickpads: Set of 25. Per fastener.

- Quicktape : Set of 25. Double-sided adhesive.

Variantes:

- 12 mm

- 16 mm

- 20 mm

- 28 mm

- 4 mm

- 40 mm

- 52 mm

- 60 mm

- Ouickramp x 25 (only)

- Quickramp x 4 (only)

- Quicktape x25 (only)

- 8 mm