

Lofoten toilet lift



- Premium Right-handed 811184.D (On restock - Available from 25/11/2025)
- Premium Left-handed 811184.G
- Basic Right-handed 811183.D
- Basic Left-handed 811183.G

- Installs without any special adjustments
- Supplied with wheels : fixed or mobile installation
- Right or left control

The Lofoten toilet lift allows users to sit down and stand up from the toilet independently and safely. By pressing the control button on one of the armrests, the seat gently raises or lowers. The Lofoten is installed over an existing toilet without any modifications or installation needed. It is supplied with 4 wheels (2 with brakes) as standard: you can choose to install it using the 4 legs (height under frame adjustable from 38.5 to 48.5 cm) or replace the legs with wheels to make it mobile (height under frame adjustable from 42 to 45 cm).

2 models available in the Lofoten range:

- The Basic model requires a permanent mains connection.
- The Premium model has a rechargeable battery with charge level indicator (approx. 100 cycles on a full charge), an ergonomic backrest and a removable potty for independant use. A remote control is supplied to control the raising and lowering of the lift. (The left-handed model does not yet have this remote control).

White zinc-plated steel frame, ABS and rubber feet. Overall dimensions: width 60.6 x depth 52.5 x height adjustable from 38.5 to 48.5 cm (with feet) or 42 to 45 cm (with wheels).

Width between armrests: 48 cm.

Backrest height: 38 cm (Premium version).

Recess: 27.5 x 23 cm. Seat height: 57.5 to 67.5 cm. Maximum user weight: 200 kg.

Variantes:

- Premium
- Basic
- Right-handed
- Left-handed

 $\textbf{Date d'impression:}\ 08/11/2025$